





A I temperature cabinet adjustable from 9 to 15° to mature your wines in the best possible conditions.



EAN Code: 3543290003742

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	5	74
Mixed Configuration	I	I	98
Minimum Configuration (100% storage)	1	I	98
Standard Configuration	1	I I	98

UNIVERSAL SHELF

Universal shelf: AOHUI

Weight: 2.6 kg Type of structure: slats

Number of bottles per level: 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



72 Bottles











« Presentation » 6 + 36 Bottles

Artevino AOHUI shelf has a label holder:



	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

- Standard configuration
- Traditional Bordeaux bottles
- Calculated with an ambient temperature of 32°C
- Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration

****** R600a gas. With a R134a gas (for US, CA, Korea, Taïwan): 38 db(A)

Range: **OXYGEN**

Model OXP1T98PPD

Fonction: Ageing

Capacity*: 98 Bottles**

A constant temperature due to the dual Heating/Cooling controls.

Optimised humidity due to the circulation of humid air.



Air circulation ensured by a breather hole located inside the cellar.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES

63.2 Gross weight, packaged(kg)* Net weight (kg)* 50.2

1090 x 720 x 760 Dimensions in packaging H x W x D (mm) Dimensions $H \times W \times D(mm)$ 960 x 680 x 700

Color scheme Tobacco

Energy efficiency rating A+ Acoustic emissions (dB(A))***** 37 Electrical power (W)*** 60 Electrical intensity (A)*** Consumption per 24h (KWh) **** 0.31 Annual energy consumption AEc* (kWh/year) **** 0 - 35°C Ambient temperature operating limit

- √ Digital electronic controls
- √ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit
- ✓ Automatic « Winter function »
- √ Temperature fault alarm icon
- √ Interior lining of dimpled aluminium
- ✓ Solid door
- √ Inox Handle
- √ Lock
- √ 2 adjustable feet
- √ Storage grid in the low part